

STAR-STREAM™

STAR-STREAM™ -24-RGB

Features

- RGB color-changing LED strips of multiple lengths
- Wide view angle of up to 105°
- High brightness and long operating life
- Low energy consumption
- Common anode configuration
- Maximum length can be extended using the SS-COUPLER™

PRODUCT SPECIFICATIONS

Product Number:	StarStream-24-RGB
LED Type:	SMD RGB LED
Input Voltage:	24VDC
LED fv = 3V: (each 20cm incl. 7 LEDs)	3Vx7 = 21V / 20cm
Max. Current/Unit:	60mA (R0mA G20mA B20mA)
Max. Watts/Unit:	1.44W
LED Quantity/Unit:	7 ea / 0.2 meters
Unit Length:	20 cm
Max. Useable Length:	PAVO-SS-24 Controller: 20 meters PAVO-DIAL-DMX Controller: 15 meters
Dimensions:	11mm x 18mm rectangular shape
Tube Material:	UV-protected PVC
Color:	Any color available with RGB color mixing
Cutting Line:	Every 0.2 meters
Controller Model:	PAVO-DIAL-DMX or PAVO-SS-24
Operation Temperature:	-20°C ~ 80°C
Power Supply: (Power Consumption for each meter = 7W)	20M: 150W/24VDC 15M: 105W/24VDC

CAUTION: The STARSTREAM-24-RGB cannot be bent in a radius smaller than 15cm or there is a risk the soldering joints will be broken.

Ver: 20080806

Taiwan Operations: Color Stars, Inc.

10F, No. 566 Jung Jeng Rd. Sindian City
Taipei County 231, Taiwan, R.O.C.

Tel: +886-2-8667-6600 Fax: +886-2-8667-1400

Email: sales@colorstars.com Website: www.colorstars.com

ColorStars Group

Headquarters:

ColorStars Group

300 Center Ave., Suite 202

Bay City, MI 48708 USA

Tel: 989-509-5924 Fax: 989-509-5924

Email: sales@colorstars.com Website: www.colorstars.com



The Star Stream™ -24-RGB is ideal for accent or cove lighting: